

Rittal – The System.

Faster – better – everywhere.

▶ LED system light - 2500110

Date : Apr 30 , 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



LED system light - 2500110

created: 04.30.2021 build on <https://www.rittal.us/>



Product Description

| | |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Version | without socket |
| Description | LED system light - the first light designed especially for enclosures! Advanced LED technology provides even more light into the last recess. |
| Benefits | A configuration to suit every application Optimum illumination of the entire enclosure Option of clip-on screw or magnetic attachment |
| Fittings | without socket |
| Material | Light body: Extruded aluminum Light cover: Polycarbonate (halogen-free) Light ends: PC-ABS (halogen-free) |
| Color | Enclosure: RAL 7016 |
| Protection category IP to IEC 60 529 | IP 20 |
| Supply includes | Assembly screws |
| Dimensions | Height: 55 mm (2.2 ") Width: 337 mm (13 ") Depth: 23 mm (0.91 ") |
| Installation options | AE CM TP: with universal bracket AE: with rail for interior installation Screw-fasten or clip directly onto the TS/SE section |
| Rated operating voltage | 100V - 240V 1~ 50Hz/60Hz |

| | |
|----------------------------|----------------------------------------------------------------------|
| Rated power Pel | 7 W |
| Luminous flux | 600 lm |
| Light color | 4000 K (neutral white) |
| Protection category | II (total insulation) |
| Connection options | Door-operated switch Power Supply 2-pole Through-wiring 2-pole |
| Light – installation type | Screw fastening Clip fastening Magnetic fastener (accessories) |
| Operating temperature | -20°C...+55°C |
| Packaging unit | 1 pc(s). |
| Weight/packaging unit | 0.35 kg (0.8 lb.) |
| EAN | 4028177806948 |
| Customs tariff number | 94054099 |
| Product description (long) | SZ System Light LED 600 Lumen L: 337 mm 100-240 V |