

Rittal – The System.

Faster – better – everywhere.

▶ LED system light - 2500310

Date : Apr 30 , 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



LED system light - 2500310

created: 04.30.2021 build on <https://www.rittal.us/>



Product Description

Version	with socket with motion detector
Description	LED system light - the first light designed especially for enclosures! Advanced LED technology provides even more light into the last recess.
Benefits	A configuration to suit every application Optimum illumination of the entire enclosure Option of clip-on screw or magnetic attachment
Fittings	90° rotating connector Adjustable light distribution Adjustable light direction Motion sensor Socket
Motion sensor	yes
Material	Light body: Extruded aluminum Light cover: Polycarbonate (halogen-free) Light ends: PC-ABS (halogen-free)
Color	Enclosure: RAL 7016
Protection category IP to IEC 60 529	IP 20
Supply includes	Assembly screws
Dimensions	Height: 85 mm (3.3 ") Width: 437 mm (17 ") Depth: 44 mm (1.7 ")

Installation options	AE CM TP: with universal bracket AE: with rail for interior installation Screw-fasten or clip directly onto the TS/SE section
Rated operating voltage	100V - 240V 1~ 50Hz/60Hz
Rated power Pel	13 W
Rated insulation voltage	300 V AC
Rated impulse withstand voltage, phase to earth	2500 V AC
Equipment (electrical)	D ground pin (type F CEE 7/3)
Luminous flux	1200 lm
Light color	4000 K (neutral white)
Protection category	II (total insulation)
Overvoltage category	II
Connection options	Power Supply 3-pole Through-wiring 3-pole
Light – installation type	Screw fastening Clip fastening
Operating temperature	-20°C...+55°C
Packaging unit	1 pc(s).
Weight/packaging unit	0.7 kg (1.5 lb.)
EAN	4028177806986
Customs tariff number	94054099
Product description (long)	SZ System Light LED 1200 Lumen L: 437 mm 100-240 V with integral motion detector