


Rittal – The System.

Faster – better – everywhere.



KX 1575.000

KX small housing

State: 9/16/2022 (Source: ittal.com/us-en)



FRIEDHELM LOH GROUP

KX 1575.000 - KX small housing E-box KX, sheet steel

The small enclosure KX, E-Box KX, carbon steel offers remarkable ease of assembly and flexibility when selecting lock systems.

Features

Model No.	KX 1575.000
Product description	The small enclosure KX, E-Box KX, carbon steel offers remarkable ease of assembly and flexibility when selecting lock systems.
Material	Housing: Carbon steel Door: Carbon steel, all-round foamed-in PU seal
Surface finish	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color	RAL 7035
Supply includes	Housing with door Mounting plate Cam lock with 3 mm double-bit insert 180° hinge
Protection category NEMA	NEMA 1, 3R, 4, 12
Protection category IP to EN 60 529	IP 66
Type rating according to UL 50E	Type 1, 3R, 4, 12
IK code	IK08
Dimensions	Width: 300 mm Height: 300 mm Depth: 155 mm Width: 11.8 " Height: 11.8 " Depth: 6.1 "

Features

Mounting plate	Width: 275 mm Height: 285 mm Width: 10.8 " Height: 11.2 "
Material thickness - enclosure	1.25 mm 0.05 "
Material thickness - door	1.25 mm 0.05 "
Material thickness – mounting plate	2 mm 0.08 "
Lock	Number locks: 1
Base material	Carbon steel
Packaging unit	1 pc(s).
Weight/packaging unit	5.5 kg 12.1 lb.
Copper weight (kg per piece)	0
Customs tariff number	94032080
EAN	4028177816619
ETIM 7.0	EC000261
ECLASS 8.0	27180101

Approvals

Approvals	Bureau Veritas DNV-GL GOST Lloyds Register of Shipping UL + C-UL (listed)
Certificates	Protection category

Approvals

Explanations

Manufacturer's declaration
Declaration of conformity
Declaration of conformity UK