



AZM300B-I2-ST-AS-A-P

- Thermoplastic enclosure
- Repeated individual coding with RFID technology
- Coding level "High" according to ISO 14119
- Suitable for hinged and sliding guards
- 3 different directions of actuation
- Actuator monitored
- Power to lock
- Solenoid supply 24 VDC (Aux)
- hygienic design
- Protection class IP 69
- Solenoid interlock with integrated AS-i Safety Interface
- Universal repeatedly teachable or individual coding because of the RFID technology
- I-variants with coding level HIGH to ISO 14119
- 2 integrated snap-in stages

Data

Ordering data

Product type description	AZM300B-I2-ST-AS-A-P
Article number (order number)	103005904
EAN (European Article Number)	4030661475059
eCl@ss number, version 12.0	27-27-26-03
eCl@ss number, version 11.0	27-27-26-03
eCl@ss number, version 9.0	27-27-26-03
ETIM number, version 7.0	EC002593
ETIM number, version 6.0	EC002593

Approvals - Standards

Certificates	TÜV cULus ASi-SaW ECOLAB EAC FCC
--------------	---

General data

Standards	EN IEC 62026-2 EN ISO 13849-1 EN ISO 14119 EN IEC 60947-5-1 EN IEC 61508
Coding	Individual coding, multiple teaching
Coding level according to EN ISO 14119	High
Working principle	RFID
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	595 g
Time to readiness, maximum	5,000 ms
Reaction time, maximum	120 ms
Duration of risk, maximum	200 ms

General data - Features

Power to lock	Yes
Actuator monitored	Yes
Latching	Yes
Manual release	Yes
Safety functions	Yes
Integral system diagnostics, status	Yes
Number of actuating directions	3

Safety classification

Standards	EN IEC 61508
Performance Level, up to	e
Category	4
PFH value	4.00×10^{-10} /h
PFD value	7.00×10^{-5}
Safety Integrity Level (SIL), suitable for applications in	3
Mission time	20 Year(s)

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Note (Mechanical life)	When using as door stop: ≥ 50.000 operations (door mass ≤ 5 kg and actuating speed ≤ 0.5 m/s)
Holding force	1,150 N
Latching force, adjustable, position 1	25 N
Latching force, adjustable, position 2	50 N

Mechanical data - Switching distances according EN IEC 60947-5-3

Assured switching distance "ON" S_{ao}	1 mm
Assured switching distance "OFF" S_{ar}	20 mm
Switch distance, typical	2 mm

Mechanical data - Connection technique

Termination	Connector plug M12, 4-pole, (A-coding)
-------------	--

Mechanical data - Dimensions

Length of sensor	34.4 mm
Width of sensor	87.4 mm
Height of sensor	102.6 mm

Ambient conditions

Degree of protection	IP67 IP69K IP66
Ambient temperature, minimum	+0 °C
Ambient temperature, maximum	+60 °C
Storage and transport temperature, minimum	-10 °C
Storage and transport temperature, maximum	+90 °C
Resistance to vibrations	10 ... 150 Hz, amplitude 0.35 mm
Resistance to shock	30 g / 11 ms
Protection class	II

Ambient conditions - Insulation values

Rated insulation voltage U_i	32 VDC
Rated impulse withstand voltage U_{imp}	0.8 kV
Overvoltage category	III
Degree of pollution	3

Electrical data - AS Interface

AS-i Operating voltage, minimum	18 VDC
AS-i Operating voltage AS-i maximum	31.6 VDC
Note (AS-i Operating voltage)	Protection against polarity reversal
AS-i Current consumption, maximum	100 mA
Rated operating voltage	18 ... 31.6 VDC (Protection against polarity reversal)

Electrical data - AS-Interface specification

AS-i Specification	Safety-Slave
AS-i Version	V 3.0
AS-i Profile	S-7.B.F.E
AS-i Input, Channel 1	Data bits DI 0 / DI 1 = dynamic code transmission
AS-i Input, Channel 2	Data bits DI 2 / DI 3 = dynamic code transmission
AS-i Outputs, DO 0	Solenoid control
AS-i Outputs, DO 1	No Function
AS-i Outputs, DO 2	No Function
AS-i Outputs, DO 3	No Function
AS-i Parameter bits, P0	Safety guard closed and can be locked
AS-i Parameter bits, P1	Solenoid interlock locked
AS-i Parameter bits, P2	Auxiliary voltage in
AS-i Parameter bits, P3	Internal device error (FID)
Note (AS-i Parameter bits)	Set the parameter outputs to "1111" (0xF) FID: periphery error
AS-i Input module address	0
Note (AS-i Input module address)	Preset to address 0, can be changed through AS-interface bus master or hand-held programming device

Electrical data - Auxiliary voltage

Rated operating voltage	24 VDC -15% / +10% (stabilised PELV)
-------------------------	--------------------------------------

Current consumption	300 mA
Operating voltage	24 VDC -15 % / 10 % (stabilised PELV power supply)

Status indication

Note (LED switching conditions display)	(1) green/red LED (AS-i duo LED): Supply voltage/communication error/slave address = 0/periphery error detected/device error detected/manipulation protection active (2) LED yellow: Device condition (Enabling status) (3) LED red: Internal device error
---	--

Pin assignment

PIN 1	AS-Interface +
PIN 2	Aux - (P)
PIN 3	AS-Interface -
PIN 4	Aux + (P)

Scope of delivery

Scope of delivery	Actuators must be ordered separately.
-------------------	---------------------------------------

Accessory

Recommendation (actuator)	AZ/AZM300-B1
---------------------------	--------------

Ordering code

Product type description:
AZM300(1)(2)-ST-AS-(3)(4)(5)

(1)

Z Guard locking monitored

B Actuator monitored

(2)

without	Standard coding
I1	Individual coding
I2	Individual coding, multiple teaching

(3)

without	Power to unlock
A	Power to lock

(4)

without	Magnet supply from AS-Interface
P	Magnet supply 24 VDC (AUX)

(5)

without	Manual release
N	Emergency release
T	Emergency exit
T8	Emergency exit, distance 8.5 mm


Pictures

Product picture (catalogue individual photo)



ID: kazm3f26
| 905.6 kB | .jpg | 352.425 x 440.619 mm - 999 x 1249 px - 72 dpi
| 59.1 kB | .png | 74.083 x 92.428 mm - 210 x 262 px - 72 dpi

Dimensional drawing basic component



ID: kazm3g02

| 7.1 kB | .png | 73.731 x 125.589 mm - 209 x 356 px - 72 dpi

| 163.3 kB | .jpg | 352.778 x 599.369 mm - 1000 x 1699 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 12/14/2022, 10:57 PM