



NAS 311 ST1-AS

- Thermoplastic actuators
- Emergency stop station
- AS-Interface M12 connector
- 85 mm x 85 mm x 97,8 mm
- Integrated AS-Interface
- Pull to reset
- Resistant to chemicals

Data

Ordering data

Product type description	NAS 311 ST1-AS
Article number (order number)	101173041
EAN (European Article Number)	4030661448831
eCl@ss number, version 12.0	27-37-12-44
eCl@ss number, version 11.0	27-37-12-44
eCl@ss number, version 9.0	27-37-12-44
ETIM number, version 7.0	EC002034
ETIM number, version 6.0	EC002034

Approvals - Standards

Certificates	TÜV ASi-SaW
--------------	----------------

General data

Standards	EN IEC 62026-2 EN ISO 13849-1 EN ISO 13850 EN IEC 60947-5-1 EN IEC 61508
Enclosure material	Plastic
Gross weight	330 g

Safety classification

Standards	EN IEC 61508
Performance Level, up to	e
Category	4
PFH value	1.40×10^{-8} /h
Note (PFH-value)	up to max. 5,000 switching cycles/year
Safety Integrity Level (SIL), suitable for applications in	3
Mission time	20 Year(s)

Mechanical data - Connection technique

Termination	Connector plug M12, 4-pole, (A-coding)
Connector position	Bottom

Mechanical data - Dimensions

Length of sensor	97.8 mm
Width of sensor	85 mm
Height of sensor	85 mm

Ambient conditions

Degree of protection	IP65
Ambient temperature, minimum	-25 °C

Ambient temperature, maximum	+60 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+85 °C
Relative humidity, minimum	30 %
Relative humidity, maximum	95 %
Note (Relative humidity)	non-condensing non-icing

Electrical data

Current consumption	50 mA
---------------------	-------

Electrical data - AS Interface

AS-i Operating voltage, minimum	26.5 VDC
AS-i Operating voltage AS-i maximum	31.6 VDC
Note (AS-i Operating voltage)	Protection against polarity reversal

Electrical data - AS-Interface specification

AS-i Version	V 2.1
AS-i Profile	S-7.B.0.E
AS-i, IO-Code	0x7
AS-i, ID-Code	0xB
AS-i, ID-Code1	0xF
AS-i, ID-Code2	0xE
AS-i Input, Channel 1	Data bits DI 0 / DI 1 = dynamic code transmission
AS-i Input, Channel 2	Data bits DI 2 / DI 3 = dynamic code transmission
AS-i Outputs, DO 0 ... DO 3	No Function
AS-i Parameter bits, P0 ... P3	No function
AS-i Input module address	0

Note (AS-i Input module address)

Preset to address 0, can be changed through AS-interface bus master or hand-held programming device

Pin assignment

PIN 1	AS-i +
PIN 2	n.c.
PIN 3	AS-Interface -
PIN 4	n.c.

Pictures

Product picture (catalogue individual photo)




ID: knas3f01

| 802.8 kB | .jpg | 352.425 x 357.011 mm - 999 x 1012 px - 72 dpi

| 49.7 kB | .png | 73.731 x 74.789 mm - 209 x 212 px - 72 dpi

Dimensional drawing basic component




ID: knas3g01

| 33.1 kB | .cdr |

| 3.6 kB | .png | 74.083 x 37.394 mm - 210 x 106 px - 72 dpi

| 91.0 kB | .jpg | 352.778 x 178.506 mm - 1000 x 506 px - 72 dpi

Contact arrangement



ID: km12-k4c

| 4.2 kB | .png | 74.083 x 74.083 mm - 210 x 210 px - 72 dpi

| 113.3 kB | .jpg | 352.778 x 352.778 mm - 1000 x 1000 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 12/13/2022, 7:02 AM