



PS216-T11-Q210

- thermoplastic enclosure with foldable latching cover
- small body
- vertical mounting
- Twisting of towing eye not possible
- Progress function (ballpoint pen principle)
- LED version available

Data

Ordering data

Product type description	PS216-T11-Q210
Article number (order number)	103032512
EAN (European Article Number)	4030661546216
eCl@ss number, version 12.0	27-27-26-01
eCl@ss number, version 11.0	27-27-26-01
eCl@ss number, version 9.0	27-27-26-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

Approvals - Standards

Certificates	cULus
	CCC
	EAC

General data

Housing construction form	Norm construction design
Material of the contacts, electrical	Silver
Length of the wire, maximum	100 m

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Mechanical data

Mechanical life, minimum	100,000 Operations
Positive break force, minimum	70 N
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	1 m/s

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, minimum	0.34 mm ²
Cable section, maximum	1.5 mm ²

Mechanical data - Dimensions

Length of sensor	32.5 mm
Width of sensor	31 mm
Height of sensor	116 mm

Ambient conditions

Degree of protection	IP67 IP66
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C
Protection class	II

Ambient conditions - Insulation values

Rated insulation voltage U_i	250 V
Rated impulse withstand voltage U_{imp}	4 kV
Overvoltage category	III
Degree of pollution	3

Electrical data

Thermal test current	10 A
Required rated short-circuit current	400 A
Utilisation category AC-15	240 VAC
Utilisation category AC-15	3 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	3 A
Switching element	1 NO contact, 1 NC contacts
Switching principle	Slow action

Ordering code

Product type description:
PS216-(1)-(2)-(3)

(1)

T11	Slow action 1 NO contact / 1 NC contact
T20	Slow action 2 NO contact
T02	Slow action 2 NC contacts

Diagram

(1) 11

(3) 23

12

24

(2)

(4)

ID: kps216k01

| 54.7 kB | .jpg | 352.778 x 106.186 mm - 1000 x 301 px - 72 dpi

| 2.8 kB | .png | 74.083 x 22.225 mm - 210 x 63 px - 72 dpi

Assembly example

2 mm

1

EN

12

24

11

23

5 mm

1

EN

12

24

11

23

5 mm

1

EN

12

24

11

23

2 mm

0

AUS

12

24

11

23

ID: kps216m01

| 157.7 kB | .jpg | 352.425 x 505.531 mm - 999 x 1433 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 12/16/2022, 2:13 AM