



RSS 36-ST-AS-R

- Universal coding with RFID technology
- with latching
- Thermoplastic enclosure
- RFID-technology for needs-based protection against tampering
- optionally with integrated magnetic latching

Data

Ordering data

Product type description	RSS 36-ST-AS-R
Article number (order number)	103001534
EAN (European Article Number)	4030661426204
eCl@ss number, version 11.0	27-27-24-03
eCl@ss number, version 9.0	27-27-24-03
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

Approvals - Standards

Certificates	TÜV cULus ASi-SaW EAC
--------------	--------------------------------

General data

Standards	EN IEC 62026-2 EN ISO 13849-1 EN ISO 14119 EN IEC 60947-5-3 EN IEC 61508
Coding	Universal coding
Coding level according to EN ISO 14119	Low
Working principle	RFID
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	g
Time to readiness, maximum	5,000 ms
Reaction time, maximum	100 ms
Duration of risk, maximum	200 ms

General data - Features

Coding	Yes
Latching	Yes
Safety functions	Yes
Integral system diagnostics, status	Yes
Number of actuating directions	3

Safety classification

Standards	EN IEC 61508
Performance Level, up to	e
Category	4
PFH value	5.13×10^{-10} /h
PFD value	3.24×10^{-5}
Safety Integrity Level (SIL), suitable for applications in	3
Mission time	20 Year(s)

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Note (Mechanical life)	Actuating speed 0.25 m/s Operations for door weights ≤ 5 kg
Hysteresis (Switching distance), maximum	2 mm
Repeat accuracy R	0.5 mm
Latching force, approx.	18 N

Mechanical data - Switching distances according EN IEC 60947-5-3

Assured switching distance "ON" S_{ao}	10 mm
Assured switching distance "OFF" S_{ar}	16 mm
Switch distance, typical	12 mm

Mechanical data - Connection technique

Termination	Connector plug M12, 4-pole, (A-coding)
-------------	--

Mechanical data - Dimensions

Length of sensor	22 mm
Width of sensor	106.3 mm
Height of sensor	25 mm

Ambient conditions

Degree of protection	IP65 IP67 IP69K
----------------------	-----------------------

Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+85 °C
Resistance to vibrations	10 ... 55 Hz, amplitude 1 mm
Resistance to shock	30 g / 11 ms
Protection class	II

Ambient conditions - Insulation values

Rated insulation voltage U_i	32 VDC
Rated impulse withstand voltage U_{imp}	0.8 kV
Overvoltage category	III
Degree of pollution	3

Electrical data

Switching frequency, maximum	1 Hz
------------------------------	------

Electrical data - AS Interface

AS-i Operating voltage, minimum	18 VDC
AS-i Operating voltage AS-i maximum	31.6 VDC
Note (AS-i Operating voltage)	Protection against polarity reversal
AS-i Current consumption, maximum	100 mA
Rated operating voltage	18 ... 31.6 VDC (Protection against polarity reversal)

Electrical data - AS-Interface specification

AS-i Specification	Safety-Slave
AS-i Version	V 3.0
AS-i Profile	S-0.B.F.E
AS-i, IO-Code	0x0
AS-i, ID-Code	0xB
AS-i, ID-Code1	0xF
AS-i, ID-Code2	0xE
AS-i Input, Channel 1	Data bits DI 0 / DI 1 = dynamic code transmission
AS-i Input, Channel 2	Data bits DI 2 / DI 3 = dynamic code transmission
AS-i Outputs, DO 0 ... DO 3	No Function
AS-i Parameter bits, P0	Actuator in
AS-i Parameter bits, P1	Enabling inhibit (tamper protection time) active (FID))
AS-i Parameter bits, P2	No function
AS-i Parameter bits, P3	Internal device error (FID)
Note (AS-i Parameter bits)	Set the parameter outputs to "1111" (0xF) FID: periphery error
AS-i Input module address	0
Note (AS-i Input module address)	Preset to address 0, can be changed through AS-interface bus master or hand-held programming device

Status indication

Note (LED switching conditions display)	(1) green/red LED (AS-i Duo LED): Supply voltage / communication error / slave address = 0 / periphery error detected / Tamper protection time active (2) yellow LED: device condition (enabling status) / hysteresis signal / device error
---	--

Pin assignment

PIN 1	AS-Interface +
PIN 2	n.c. (≤ 30 VDC)
PIN 3	AS-Interface -
PIN 4	n.c. (≤ 30 VDC)

Scope of delivery

Scope of delivery Actuators must be ordered separately.

Accessory

Recommendation (actuator) RST 36-1-R

Ordering code

Product type description:
RSS 36-(1)-ST-AS-(2)

(1)

without	Standard coding
AD	Standard coding, actuator detection
I1	Individual coding
I2	Individual coding, for multiple applications

(2)

without	without latching
R	with latching, latching force approx. 18 N


Pictures

Product picture (catalogue individual photo)



ID: krss3f06
| 836.3 kB | .jpg | 229.658 x 625.122 mm - 651 x 1772 px - 72 dpi
| 122.8 kB | .png | 74.083 x 201.436 mm - 210 x 571 px - 72 dpi

Dimensional drawing basic component



ID: krss3g03

| 97.2 kB | .jpg | 352.778 x 175.683 mm - 1000 x 498 px - 72 dpi

| 1.9 kB | .png | 74.083 x 37.042 mm - 210 x 105 px - 72 dpi

| 6.2 kB | .png | 50.038 x 24.892 mm - 591 x 294 px - 300 dpi

| 19.4 kB | .jpg | 196.144 x 97.719 mm - 556 x 277 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 12/15/2022, 3:15 AM