



NO IMAGE
AVAILABLE

RSS32S2

Data

Ordering data

Note (Delivery capacity)	Not available!
Product type description	RSS32S2
Article number (order number)	101195366
EAN (European Article Number)	4030661487175
eCl@ss number, version 12.0	27-37-12-13
eCl@ss number, version 11.0	27-37-12-13
eCl@ss number, version 9.0	27-37-12-13
ETIM number, version 7.0	EC000222
ETIM number, version 6.0	EC000222

General data

Standards	EN IEC 60947-5-1 EN IEC 60947-1
Versions	Key - Selector switch - Front plate mounting
Installation conditions (mechanical)	arbitrarily

Sealing type	Membrane Lip gaskets Form seals
Material of the cylinder lock	Steel
Material of the front ring	Aluminium
Colour of the cylinder lock	Silver
Colour of the front ring	Silver
Gross weight	100 g

General data - Features

Latching	Yes
Fully insulated	Yes
Number of plunger	2
Number of switch positions	3

Mechanical data

Unlocking	Rotating unlatcher
Key withdrawal position	Position 0
Latching position	right left
Mechanical life, minimum	300,000 Operations
Switching angle, left	90 °
Switching angle, right	90 °
Mounting	Mounting flange EFM
Tightening torque of the screw	0.6 Nm

Mechanical data - Dimensions

Diameter total	39.5 mm
Diameter of the front ring	39.5 mm
diameters for the cylinder lock	22 mm

Diameter hole	22.3 mm
Diameter hole, with tolerance indication	22.3 + 0.4 mm
Height with key inserted	58 mm
Thickness, of the front panel, minimum	1 mm
Thickness of the front panel, maximum	6 mm
Spacing	50 x 60 mm

Ambient conditions

Degree of protection	IP65
Ambient temperature, minimum	+0 °C
Ambient temperature, maximum	+75 °C
Resistance to shock	50 g

Scope of delivery

Scope of delivery	2 keys
-------------------	--------

Note

Note (General)	Special closure on request
----------------	----------------------------

Pictures


Product picture (catalogue individual photo)



NO IMAGE
AVAILABLE

ID: no-pic01
| 98.4 kB | .jpg | 352.778 x 352.778 mm - 1000 x 1000 px - 72 dpi
| 3.3 kB | .png | 74.083 x 74.083 mm - 210 x 210 px - 72 dpi

Dimensional drawing basic component




ID: 1rss-g01

| 60.8 kB | .cdr |

| 5.0 kB | .png | 74.083 x 51.506 mm - 210 x 146 px - 72 dpi

| 54.3 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 px - 72 dpi

Diagram



ID: krss-k02

| 1,022.0 kB | .ai | 70 x 70 mm - 198 x 198 px - 72 dpi

| 78.0 kB | .jpg | 352.778 x 226.483 mm - 1000 x 642 px - 72 dpi

| 4.8 kB | .png | 74.083 x 47.625 mm - 210 x 135 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 12/13/2022, 5:58 AM