

Product availability : Non-Stock - Not normally stocked in distribution facility



Price** : 7,569.00 USD



Main

Product	Single Throw Safety Switch
Current Rating	600 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Short Circuit Current Rating	100 kA T
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	General duty
Voltage Rating	240 V AC
Wire Size	AWG 4...500 kcmil aluminium/copper

Complementary

Width	638.30 mm (25.13 in)
Height	1247.90 mm (49.13 in)
Depth	225.55 mm (8.88 in)
Tightening torque	50.84 N.m (450 lbf.in) AWG 4...500 kcmil)

Ordering and shipping details

Category	00059 - MISC G/D SWITCHES
Discount Schedule	DE1A
GTIN	00785901003717
Package weight(Lbs)	60.33 kg (133 lb(US))
Returnability	No
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------