

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\*\* : 20,015.00 USD



### Main

Product	Single Throw Safety Switch
Current Rating	1200 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R/12 galvanized steel
Factory Installed Neutral	Neutral (factory installed)
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	200 kA maximum L
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	250 V DC 240 V AC
Wire Size	AWG 3/0...750 kcmil copper or aluminium

### Complementary

Width	930.15 mm (36.62 in)
Height	1755.90 mm (69.13 in)
Depth	450.85 mm (17.75 in)
Tightening torque	42.37 N.m (375 lbf.in) 0.13...0.59 in <sup>2</sup> (85.01...380 mm <sup>2</sup> ) AWG 3/0...750 kcmil)

### Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A
Discount Schedule	DE1
GTIN	00785901046448
Package weight(Lbs)	167.83 kg (370 lb(US))
Returnability	No

---

Country of origin	MX
-------------------	----

---

### Offer Sustainability

---

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

---

### Contractual warranty

---

Warranty	18 months
----------	-----------

---