

H361N

SWITCH FUSIBLE HD 600V 30A 3P NEUTRAL

Product availability : Stock - Normally stocked in distribution facility



Price** : 617.00 USD



Main

Product	Single Throw Safety Switch
Current Rating	30 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1 steel
Factory Installed Neutral	Neutral (factory installed)
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 kA H or K 200 kA R, J or L
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	600 V AC/DC
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper

Complementary

Width	191.77 mm (7.55 in)
Height	370.84 mm (14.6 in)
Depth	123.70 mm (4.87 in)
Tightening torque	5.08 N.m (45 lbf.in) 0.02 in ² (13.3 mm ²) AWG 6 4.52 N.m (40 lbf.in) 0.01 in ² (8.367 mm ²) AWG 8 3.95 N.m (35 lbf.in) 0.00...0.01 in ² (2.06...5.261 mm ²) AWG 14...AWG 10)

Ordering and shipping details

Category	00008 - H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE1
GTIN	00785901481911

Package weight(Lbs)	3.74 kg (8.25 lb(US))
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------

Technical drawing of a 125mm wide, 100mm high, 100mm deep metal enclosure with three knockouts. The drawing includes three views: front, side, and top. Dimensions are given in inches and millimeters. The front view shows a central knockout (A) and two side knockouts (B and C). The side view shows the depth of the enclosure and the position of the knockouts. The top view shows the layout of the knockouts and the mounting surface. A table of knockout dimensions is provided at the bottom right.

Dimensions (inches and millimeters):

- Overall width: 6.51 [165]
- Overall height: 14.60 [371]
- Overall depth: 4.87 [124]
- Knoutout A diameter: .31 [8] DIA (2 HOLES)
- Knoutout B diameter: .31 [8] DIA (2 HOLES)
- Knoutout C diameter: .31 [8] DIA (2 HOLES)
- Knoutout D diameter: .31 [8] DIA (2 HOLES)
- Knoutout E diameter: .31 [8] DIA (2 HOLES)
- Knoutout F diameter: .31 [8] DIA (2 HOLES)
- Knoutout G diameter: .31 [8] DIA (2 HOLES)
- Knoutout H diameter: .31 [8] DIA (2 HOLES)
- Knoutout I diameter: .31 [8] DIA (2 HOLES)
- Knoutout J diameter: .31 [8] DIA (2 HOLES)
- Knoutout K diameter: .31 [8] DIA (2 HOLES)
- Knoutout L diameter: .31 [8] DIA (2 HOLES)
- Knoutout M diameter: .31 [8] DIA (2 HOLES)
- Knoutout N diameter: .31 [8] DIA (2 HOLES)
- Knoutout O diameter: .31 [8] DIA (2 HOLES)
- Knoutout P diameter: .31 [8] DIA (2 HOLES)
- Knoutout Q diameter: .31 [8] DIA (2 HOLES)
- Knoutout R diameter: .31 [8] DIA (2 HOLES)
- Knoutout S diameter: .31 [8] DIA (2 HOLES)
- Knoutout T diameter: .31 [8] DIA (2 HOLES)
- Knoutout U diameter: .31 [8] DIA (2 HOLES)
- Knoutout V diameter: .31 [8] DIA (2 HOLES)
- Knoutout W diameter: .31 [8] DIA (2 HOLES)
- Knoutout X diameter: .31 [8] DIA (2 HOLES)
- Knoutout Y diameter: .31 [8] DIA (2 HOLES)
- Knoutout Z diameter: .31 [8] DIA (2 HOLES)

Knoutout Dimensions Table:

SYMBOL	CONDUIT SIZE		DIAMETER	
	IN	MM	IN	MM
A	.50	13	.88	22
B	.75	19	1.13	29
C	1.00	25	1.38	35
D	1.25	32	1.75	44