

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\*\* : 3,968.00 USD



### Main

|                              |                                                   |
|------------------------------|---------------------------------------------------|
| Product                      | Single Throw Safety Switch                        |
| Current Rating               | 60 A                                              |
| Certifications               | UL listed file E2875                              |
| Enclosure Rating             | NEMA 4X fiberglass reinforced polyester           |
| Factory Installed Neutral    | None                                              |
| Disconnect Type              | Fusible disconnect                                |
| Short Circuit Current Rating | 10 kA H or K<br>200 kA R, J or L                  |
| Mounting Type                | Surface                                           |
| Number of Poles              | 3                                                 |
| Electrical Connection        | Lugs                                              |
| Duty Rating                  | Heavy duty                                        |
| Voltage Rating               | 600 V AC/DC                                       |
| Wire Size                    | AWG 14...AWG 3 copper<br>AWG 12...AWG 3 aluminium |

### Complementary

|                   |                                                                                                                                                                                                                                                      |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Width             | 279.40 mm (11 in)                                                                                                                                                                                                                                    |
| Height            | 419.10 mm (16.5 in)                                                                                                                                                                                                                                  |
| Depth             | 223.52 mm (8.8 in)                                                                                                                                                                                                                                   |
| Tightening torque | 5.65 N.m (50 lbf.in) AWG 3)<br>5.08 N.m (45 lbf.in) AWG 6...AWG 4)<br>4.52 N.m (40 lbf.in) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) AWG 8)<br>5.65 N.m (50 lbf.in) 0.00...0.01 in <sup>2</sup> (2.06...5.261 mm <sup>2</sup> ) AWG 14...AWG 10) |

### Ordering and shipping details

|                   |                                   |
|-------------------|-----------------------------------|
| Category          | 00111 - H&HU SW,N4X(DF,DX)NON-MET |
| Discount Schedule | DE1                               |

|                     |                        |
|---------------------|------------------------|
| GTIN                | 00785901627852         |
| Package weight(Lbs) | 9.65 kg (21.28 lb(US)) |
| Returnability       | Yes                    |
| Country of origin   | MX                     |

### Offer Sustainability

|                            |                                                                                                                        |
|----------------------------|------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                  |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                      |
| REACH free of SVHC         | Yes                                                                                                                    |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                       |
| Mercury free               | Yes                                                                                                                    |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                    |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                          |
| Circularity Profile        | No need of specific recycling operations                                                                               |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|