

H363DF

SW FUSIBLE HD 100A 3P NEMA4X FIBERGLASS

Product availability : Non-Stock - Not normally stocked in distribution facility



Price** : 7,613.00 USD



Main

Product	Single Throw Safety Switch
Current Rating	100 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 4X fiberglass reinforced polyester
Factory Installed Neutral	None
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 kA H or K 200 kA R, J or L
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	600 V AC/DC
Wire Size	AWG 12...AWG 1/0 aluminium AWG 14...AWG 1/0 copper

Complementary

Width	347.98 mm (13.7 in)
Height	629.41 mm (24.78 in)
Depth	304.80 mm (12 in)
Tightening torque	5.65 N.m (50 lbf.in) AWG 1...AWG 3/0 5.08 N.m (45 lbf.in) AWG 6...AWG 4 4.52 N.m (40 lbf.in) 0.01 in ² (8.367 mm ²) AWG 8 3.95 N.m (35 lbf.in) 0.00...0.01 in ² (2.06...5.261 mm ²) AWG 14...AWG 10

Ordering and shipping details

Category	00111 - H&HU SW,N4X(DF,DX)NON-MET
----------	-----------------------------------

Discount Schedule	DE1
GTIN	00785901627869
Package weight(Lbs)	20.41 kg (45 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------