

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\*\* : 28,316.00 USD



### Main

Product	Single Throw Safety Switch
Current Rating	200 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 4/4X/5 stainless steel 304
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect
Short Circuit Current Rating	200 kA maximum
Mounting Type	Surface
Number of Poles	6
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	600 V AC
Wire Size	AWG 6...250 kcmil copper or aluminium

### Complementary

Width	641.35 mm (25.25 in)
Height	736.60 mm (29 in)
Depth	225.55 mm (8.88 in)
Tightening torque	31.07 N.m (275 lbf.in) 0.02...0.20 in <sup>2</sup> (13.3...127 mm <sup>2</sup> ) AWG 6...250 kcmil)

### Ordering and shipping details

Category	00115 - H&HU SW,4&6P,N4,SS 30-200A
Discount Schedule	DE1
GTIN	00785901078081
Package weight(Lbs)	4.54 kg (10 lb(US))
Returnability	No
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------