

# Product data sheet

## Characteristics

# H362DSWC

## SWITCH FUSIBLE HD 60A STNLESS/CR-HI REC

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\*\* : 7,749.00 USD



### Main

Product	Receptacle Switch
For Use With	Plug APJ6485 Crouse-Hinds Arktite
Current Rating	60 A
Enclosure Rating	NEMA 4/4X/5 stainless steel 304
Horsepower Rating	30 hp 480 V AC 50 hp 600 V AC
Disconnect Type	Fusible disconnect switch
Short Circuit Current Rating	200 kA 10 kA
Mounting Type	Surface
Number of Poles	3
Phase	3 phase
Electrical Connection	Receptacle
Certifications	UL listed
Voltage Rating	600 V AC 250 V DC
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Wire Configuration	4-wire

### Complementary

Width	274.07 mm (10.79 in)
Height	428.50 mm (16.87 in)
Depth	129.79 mm (5.11 in)
Tightening torque	5.08 N.m (45 lbf.in) AWG 6...AWG 4) 4.52 N.m (40 lbf.in) AWG 8) 3.95 N.m (35 lbf.in) AWG 14...AWG 10)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Ordering and shipping details

Category	00118 - H&HU SW,W/C-HINDS RECPT-WC
Discount Schedule	DE1
GTIN	00785901076995
Package weight(Lbs)	11.34 kg (25 lb(US))
Returnability	No
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------