

HU362AWH

SW UNFUSED HD 60A/HUBBELLOCK RECEPTACLE

Product availability : Non-Stock - Not normally stocked in distribution facility



Price** : 2,310.00 USD



Main

Product	Receptacle Switch
For Use With	Plug SD12781 Hubbellock
Current Rating	60 A
Enclosure Rating	NEMA 12 galvanized steel
Horsepower Rating	50 hp 480 V AC 60 hp 600 V AC
Disconnect Type	Non-fusible disconnect switch
Short Circuit Current Rating	10 kA
Mounting Type	Surface
Number of Poles	3
Phase	3 phase
Electrical Connection	Receptacle
Certifications	UL listed
Voltage Rating	600 V AC 250 V DC
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Wire Configuration	4-wire

Complementary

Width	266.70 mm (10.5 in)
Height	419.10 mm (16.5 in)
Depth	177.80 mm (7 in)
Tightening torque	5.08 N.m (45 lbf.in) AWG 6...AWG 4) 4.52 N.m (40 lbf.in) AWG 8) 3.95 N.m (35 lbf.in) AWG 14...AWG 10)

Ordering and shipping details

Category	00119 - H&HU SW,W/HUBBELL RECPT-WH
Discount Schedule	DE1
GTIN	00785901505068
Package weight(Lbs)	9.08 kg (20.01 lb(US))
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------