

Product availability : Non-Stock - Not normally stocked in distribution facility



Price** : 331.00 USD



Main

Control button type	Standard momentary stop
Device application	Conveyor systems Presses Test laboratories Woodworking equipment Transfer machines Textiles Packaging Paint lines
Device short name	XY2
Enclosure type	Dust and damp proof weatherproof enclosure indoor/outdoor

Complementary

Line Rated Current	10 A
Cable entry	3 entries tapped for 1/2" NPT cable gland
Contact code designation	A300 Q300
Contact operation	Snap action
Contacts type and composition	2 NO/2 NC
Depth	104.14 mm (4.1 in)
Device mounting	Surface
Height	142.24 mm (5.6 in)
Installation direction	Left
Permissible voltage	300 V

Environment

NEMA degree of protection	NEMA 1/4/12
Product certifications	CSA LR44087 class 3211 03 UL listed file E164353 CCN NKCR CE

Ordering and shipping details

Category	22441 - LIMIT SWITCHES,CABLE PULL
Discount Schedule	T
GTIN	00785901162582
Package weight(Lbs)	1.04 kg (2.3 lb(US))
Returnability	No
Country of origin	MA

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------