

Product data sheet

Characteristics

1.5S1FSS

TRFMER DRY 1PH 1.5KVA 240X480V-120/240V



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1778.00 USD

Main

Product or component type	Dry Sealed Transformer
Primary voltage	240 x 480 V 120/240 V
Number of tap-offs	0

Complementary

Box number	8A
Phase	1 phase
Rated power in VA	1.5 KVA
Temperature rise	115 °C
Height	8.25 in (209.55 mm)
Width	8.68 in (220.47 mm)
Depth	6.56 in (166.62 mm)
Enclosure mounting	Wall mounted
Enclosure material	Stainless Steel

Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	UL Listed CULus CSA

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2
GTIN	00785901140894
Nbr. of units in pkg.	1
Package weight(Lbs)	30.1 Lb(US) (13.65 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**