

Product data sheet

Characteristics

10S67F

TRANSFORMER DRY 1 PHASE 10 KVA

110/220V SECONDARY



Product availability: Stock - Normally stocked in distribution facility

Price*: 4004.00 USD



Main

Product or Component Type	Dry Sealed Transformer
Primary voltage	190/200/208/220 x 380/400/416/440 V 110/220 V
Number of tap-offs	0

Complementary

Box number	13B
Phase	1 phase
Rated power in VA	10 KVA
Temperature rise	115 °C
Maximum Height	14.75 In (374.65 mm)
Maximum Width	9.75 In (247.65 mm)
Maximum Depth	11.75 In (298.45 mm)
Enclosure mounting	Wall mounted
Enclosure Material	Painted sheet steel

Environment

Insulation temperature	356 °F (180 °C)
Product Certifications	CSA UL Listed CULus TÜV

Ordering and shipping details

Category	16277 - RESIN LVGP XFRM
Discount Schedule	PE2
GTIN	00785901069508
Nbr. of units in pkg.	1
Package weight(Lbs)	165.00 Lb(US) (74.843 kg)

Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	15.00 In (38.1 cm)
Package 1 width	12.00 In (30.48 cm)
Package 1 Length	10.00 In (25.4 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**