

Product data sheet

Characteristics

10S6F

TRFMR DRY 1PH 10KVA 120X240V-120/240V



Price*: 3992.00 USD

Main

Product or Component Type	Dry Sealed Transformer
Primary voltage	120 x 240 V 120/240 V
Number of tap-offs	0

Complementary

Box number	13B
Phase	1 phase
Rated power in VA	10 KVA
Temperature rise	115 °C
Maximum Height	14.75 In (374.65 mm)
Maximum Width	9.75 In (247.65 mm)
Maximum Depth	11.75 In (298.45 mm)
Enclosure mounting	Wall mounted
Enclosure Material	Painted sheet steel

Environment

NEMA Degree of Protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product Certifications	UL Listed CULus CSA

Ordering and shipping details

Category	16277-RESIN LVGP XFMR
Discount Schedule	PE2
GTIN	00785901555537
Package weight(Lbs)	165.00 Lb(US) (74.843 kg)
Returnability	No
Country of origin	US

Packing Units

Package 1 Height	11.22 In (28.499 cm)
Package 1 width	10.24 In (26.010 cm)
Package 1 Length	13.23 In (33.604 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration

Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	----------------