

Product data sheet

Characteristics

15S3HNV
TRFMR DRY 1PH 15KVA 240X480V-120/240V



Price*: 5042.00 USD



Main

Product or component type	Non-Ventilated Transformer
Box number	17E
Insulation temperature	428 °F (220 °C)
Phase	1 phase
Primary voltage	240 x 480 V
Rated power in VA	15 KVA
Secondary voltage	120/240 V
Number of tap-offs	6 2.5 % 2+ 4-
Temperature rise	150 °C
Material	Aluminium

Ordering and shipping details

Category	16273-NON VENT NON RESIN LVGP
Discount Schedule	PE2
GTIN	00785901181293
Package weight(Lbs)	200.00 Lb(US) (90.718 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation

 China RoHS Declaration

Environmental Disclosure

 Product Environmental Profile

Contractual warranty

Warranty

18 months

Product Life Status : **Commercialised**