

Product data sheet

Characteristics

15T2FSS

TRANSFORMER DRY 3PH 15KVA

480V-208Y/120V



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 7726.00 USD



Main

Product or component type	Dry Sealed Transformer
Primary voltage	480 V delta 208Y/120 V
Number of tap-offs	2 5 % FCBN

Complementary

Box number	14C
Phase	3 phase
Rated power in VA	15 KVA
Temperature rise	115 °C
Height	14.75 In (374.65 mm)
Width	19.1 In (485.14 mm)
Depth	12.25 In (311.15 mm)
Enclosure mounting	Wall mounted
Enclosure material	Stainless Steel

Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	CSA UL Listed CULus

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2
GTIN	00785901121473
Nbr. of units in pkg.	1
Package weight(Lbs)	335 Lb(US) (151.95 kg)

Returnability	No
Country of origin	US

Packing Units

Package 1 Height	14.10 In (35.814 cm)
Package 1 width	15.30 In (38.862 cm)
Package 1 Length	19.10 In (48.514 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**