

Product data sheet

Characteristics

15T75F

TRANSFORMER DRY 3PH 15KVA 480V-240V



Product availability: Stock - Normally stocked in distribution facility

Price*: 4644.00 USD



Main

Product or Component Type	Dry Sealed Transformer
Primary voltage	480 V delta 240 V delta
Number of tap-offs	4 2.5 % FCBN

Complementary

Box number	14C
Phase	3 phase
Rated power in VA	15 KVA
Temperature rise	115 °C
Maximum Height	14.75 in (374.65 mm)
Maximum Width	19.1 in (485.14 mm)
Maximum Depth	12.25 in (311.15 mm)
Enclosure mounting	Wall mounted
Enclosure Material	Painted sheet steel

Environment

NEMA Degree of Protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product Certifications	CSA UL Listed CULus

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2
GTIN	00785901358053
Nbr. of units in pkg.	1
Package weight(Lbs)	326.00 Lb(US) (147.871 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. *Prices are indicative. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	14.75 In (37.465 cm)
Package 1 width	19.10 In (48.514 cm)
Package 1 Length	12.25 In (31.115 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**