

Product data sheet

Characteristics

2510FW1

Manual Starter, fractional horsepower, 16A, 1 pole, 1 HP at 277 VAC, no indicator, NEMA 4 enclosure, 1 conduit opening



Product availability: Stock - Normally stocked in distribution facility

Price*: 336.29 USD



Main

| | |
|---------------------------|----------------------------|
| Product or component type | Single Unit Manual Starter |
| Range of product | F |
| Thermal overload type | Melting alloy |

Complementary

| | |
|--------------------------------|---|
| Line Rated Current | 16 A |
| Cable entry | 0.75 NPT (bottom) |
| Maximum Horse Power Rating | 1 Hp 115 V AC 1 Hp 230 V AC 1 Hp 277 V AC |
| [Ue] rated operational voltage | 277 V AC |
| Poles description | 1P |
| Control type | Toggle switch (with lock-off) |
| Phase | 1 phase |
| Local signalling | No indicator |
| Reset | Manual |
| Motor starter type | Non reversing |
| Electrical connection | Screw clamp terminals |
| AWG gauge | AWG 14...AWG 12 copper |
| Height | 4.38 In (111.25 mm) |
| Width | 3 In (76.20 mm) |
| Depth | 4.25 In (107.95 mm) |

Environment

| | |
|---------------------------|---|
| Product certifications | UL listed file E42243 CCN NLRV CSA LR25490 class 3211 05 |
| NEMA degree of protection | NEMA 4 die cast zinc alloy standard size |

Ordering and shipping details

| | |
|-----------------------|--------------------------|
| Category | 21101 - 2510,2511,2512 F |
| Discount Schedule | CP1 |
| GTIN | 00785901554332 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 2.87 Lb(US) (1.3 kg) |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------|-------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 3.58 In (9.1 cm) |
| Package 1 width | 4.69 In (11.9 cm) |
| Package 1 Length | 5.39 In (13.7 cm) |

Offer Sustainability

| | |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Not compliant |
| China RoHS Regulation | China RoHS Declaration |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**