

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 201.00 USD



Commercial status

This Product is Obsolete : JUL 12, 2021

 This Product is Obsolete

Main

| | |
|------------------------------|-----------------------------|
| Range | Multi 9 |
| Product or component type | Undervoltage release |
| Device short name | MN |
| [Uc] control circuit voltage | 24 V AC 50/60 Hz 24 V DC |
| Control type | Standard |
| 9 mm pitches | 2 |

Complementary

| | |
|-------------------------|--|
| Range compatibility | Multi 9 C60 Multi 9 C60H-DC |
| Local signalling | Action indicator |
| Mounting mode | Fixed |
| Mounting support | 35 mm symmetrical DIN rail |
| Height | 3.25 In (82.5 mm) |
| Width | 0.71 In (18 mm) |
| Depth | 2.68 In (68 mm) |
| Connections - terminals | Pad terminal - 1 0.00 in ² (2.5 mm ²) - flexible Pad terminal - 1 0.00 in ² (2.5 mm ²) - rigid Pad terminal - 2 0.00 in ² (1.5 mm ²) - flexible Pad terminal - 2 0.00 in ² (1.5 mm ²) - rigid |
| Wire stripping length | 0.35 In (9 mm) |
| Tightening torque | 8.85 Lbf.In (1 N.m) |

Environment

| | |
|---------------------------------------|----------------------------------|
| Standards | EN/IEC 60947-5-1 |
| Product certifications | KEMA ASEFA LCIE ASTA |
| Tropicalisation | 2 conforming to EN/IEC 60947-5-1 |
| Relative humidity | 95 % 131 °F (55 °C) |
| Ambient air temperature for operation | -13...122 °F (-25...50 °C) |
| Ambient air temperature for storage | -40...185 °F (-40...85 °C) |

Ordering and shipping details

| | |
|-----------------------|---------------------------------------|
| Category | 00908 - C60N SUPPLEMENTARY PROTECTORS |
| Discount Schedule | DE2 |
| GTIN | 00785901595670 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 2.54 Oz (72 g) |
| Returnability | No |
| Country of origin | BE |

Packing Units

| | |
|------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 3.54 In (9 cm) |
| Package 1 width | 0.94 In (2.4 cm) |
| Package 1 Length | 3.15 In (8 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **End of commercialisation**

27108 may be replaced by any of the following products:



M9A27108

Multi9 - undervoltage release - MN - 24 V AC - 24 V DC

Qty 1

Substitution date: |