

# Product data sheet

## Characteristics

# 2S51F

Low Voltage Transformer, Resin filled, 1 Phase,  
2 kVA, 600 primary / 240/120V secondary, AL,  
115°C Rise



Product availability: Stock - Normally stocked in distribution facility

Price\*: 940.00 USD



### Main

Product or Component Type	Dry Sealed Transformer
Primary voltage	600 V 120/240 V
Number of tap-offs	0

### Complementary

Box number	9A
Phase	1 phase
Rated power in VA	2 KVA
Temperature rise	115 °C
Maximum Height	9.56 In (242.82 mm)
Maximum Width	8.68 In (220.47 mm)
Maximum Depth	6.56 In (166.62 mm)
Enclosure mounting	Wall mounted
Enclosure Material	Painted sheet steel

### Environment

NEMA Degree of Protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product Certifications	CULus UL Listed CSA

## Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2
GTIN	00785901020356
Nbr. of units in pkg.	1
Package weight(Lbs)	49.5 Lb(US) (22.45 kg)
Returnability	Yes
Country of origin	US

## Packing Units

Package 1 Height	9.30 In (23.622 cm)
Package 1 width	11.20 In (28.448 cm)
Package 1 Length	12.90 In (32.766 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**