

# Product data sheet

## Characteristics

# 2S82F

## TRANSFORMER DRY 1PH 2KVA

### 240X480V-24/48V



Product availability: Stock - Normally stocked in distribution facility

Price\*: 1500.00 USD

### Main

Product or Component Type	Buck and Boost Transformer
Box number	9A
NEMA Degree of Protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Primary Voltage	240 x 480 V
Rated power in VA	2 KVA
Secondary Voltage	24/48 V
Temperature rise	115 °C

### Ordering and shipping details

Category	16265 - BUCK & BOOST
Discount Schedule	PE2
GTIN	00785901993506
Nbr. of units in pkg.	1
Package weight(Lbs)	49.5 Lb(US) (22.45 kg)
Returnability	Yes
Country of origin	US

### Packing Units

Package 1 Height	9.70 In (24.638 cm)
Package 1 width	11.10 In (28.194 cm)
Package 1 Length	12.50 In (31.750 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<input checked="" type="checkbox"/> <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> <a href="#">China RoHS Declaration</a>
Environmental Disclosure	<input checked="" type="checkbox"/> <a href="#">Product Environmental Profile</a>
PVC free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. \*Prices are indicative. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

**Contractual warranty**

Warranty 18 months

**Product Life Status :** Commercialised