

# Product data sheet

## Characteristics

# 30T2FSS

## TRANSFORMER DRY 3PH 30KVA

### 480V-208Y/120V



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 13022.00 USD



### Main

Product or component type	Dry Sealed Transformer
Primary voltage	480 V delta 208Y/120 V
Number of tap-offs	2 5 % FCBN

### Complementary

Box number	16C
Phase	3 phase
Rated power in VA	30 KVA
Temperature rise	115 °C
Height	22 In (558.80 mm)
Width	25 In (635.00 mm)
Depth	13.5 In (342.90 mm)
Enclosure mounting	Wall mounted
Enclosure material	Stainless Steel

### Environment

NEMA degree of protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	CULus CSA UL Listed

### Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2
GTIN	00785901015376
Nbr. of units in pkg.	1
Package weight(Lbs)	775 Lb(US) (351.53 kg)

Returnability	No
Country of origin	US

### Packing Units

Package 1 Height	16.40 In (41.656 cm)
Package 1 width	25.50 In (64.770 cm)
Package 1 Length	21.30 In (54.102 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
PVC free	Yes

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**