

# Product data sheet

## Characteristics

### 30T2F

Low Voltage Transformer, Resin filled, 3 Phase,  
30 kVA, 480V Delta primary / 208Y/120V  
secondary, 115°C Rise



Product availability: Stock - Normally stocked in distribution facility

Price\*: 8536.00 USD



## Main

Product or Component Type	Dry Sealed Transformer
Primary voltage	480 V delta 208Y/120 V
Number of tap-offs	2 5 % FCBN

## Complementary

Box number	16C
Phase	3 phase
Rated power in VA	30 KVA
Temperature rise	115 °C
Maximum Height	22 In (558.80 mm)
Maximum Width	25 In (635.00 mm)
Maximum Depth	13.5 In (342.90 mm)
Enclosure mounting	Wall mounted
Enclosure Material	Painted sheet steel

## Environment

NEMA Degree of Protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product Certifications	CULus CSA UL Listed

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. \*Prices are indicative.

## Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2
GTIN	00785901039402
Nbr. of units in pkg.	1
Package weight(Lbs)	780 Lb(US) (353.80 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Package 1 Height	16.40 In (41.656 cm)
Package 1 width	25.50 In (64.770 cm)
Package 1 Length	21.30 In (54.102 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**