

Product data sheet

Characteristics

30T3HNV

TRANSFORMER DRY 3PH 30KVA

480V-208Y/120V



Product availability: Stock - Normally stocked in distribution facility

Price*: 8090.00 USD



Main

Product or component type	Non-Ventilated Transformer
Box number	19E
Insulation temperature	428 °F (220 °C)
Phase	3 phase
Primary voltage	480 V delta
Rated power in VA	30 KVA
Secondary voltage	208Y/120 V
Number of tap-offs	6 2.5 % 2+ 4-
Temperature rise	150 °C
Material	Aluminium

Ordering and shipping details

Category	16273 - NON VENT NON RESIN LVGP
Discount Schedule	PE2
GTIN	00785901181316
Nbr. of units in pkg.	1
Package weight(Lbs)	1 Lb(US) (0.45 kg)
Returnability	No
Country of origin	US

Packing Units

Package 1 Height	3.58 Ft (1.090 m)
Package 1 width	2.62 Ft (0.798 m)
Package 1 Length	1.77 Ft (0.538 m)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**