

Product data sheet

Characteristics

3S82F

Low Voltage Transformer, Resin filled, 1 Phase, 3 kVA, 240 x 480 primary / 48/24V secondary, AL, 115°C Rise



Product availability: Stock - Normally stocked in distribution facility

Price*: 2072.00 USD



Main

Product or Component Type	Buck and Boost Transformer
Box number	10A
NEMA Degree of Protection	NEMA 3R
Insulation temperature	356 °F (180 °C)
Primary Voltage	240 x 480 V
Rated power in VA	3 KVA
Secondary Voltage	24/48 V
Temperature rise	115 °C

Ordering and shipping details

Category	16265 - BUCK & BOOST
Discount Schedule	PE2
GTIN	00785901412977
Nbr. of units in pkg.	1
Package weight(Lbs)	59.50 Lb(US) (26.989 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	12.40 In (31.496 cm)
Package 1 width	11.50 In (29.21 cm)
Package 1 Length	17.20 In (43.688 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**