

Product data sheet

Characteristics

50442

closed toroid A type, for VigiPacT and Vigilhom, GA300, inner diameter 300 mm, rated current 630 A



Price*: 2295.00 USD



Main

Range	VigiPacT
Device short name	GA300
Product or component type	Earth leakage current sensor
Device application	Equipment monitoring and control
Range compatibility	RH10M residual current protection relay RH10P residual current protection relay RH21M residual current protection relay RH21P residual current protection relay RH68M residual current protection relay RH86M residual current protection relay RH86P residual current protection relay RH99M residual current protection relay RH99P residual current protection relay RH197M residual current protection relay RH197P residual current protection relay RHU residual current protection relay RHUs residual current protection relay RMH residual current protection relay
Current transformer type	A type closed toroid
[Ie] rated operational current	630 A

Complementary

Transformer ratio	1/1000
Network type	AC/DC
Network frequency	45...440 Hz
[Icw] rated short-time withstand current	100 KA 0.5 s
Residual short-circuit withstand current	85 KA / 0.5 s IEC 60947-2
[Ui] rated insulation voltage	1000 V
Overvoltage category	IV
[Uimp] rated impulse withstand voltage	12 KV
Mounting mode	Fixed cables)
Connections - terminals	Connection by clip 0.01 in ² (6.35 mm ²)
Diameter	Inner 11.46 in (291 mm)

Cable outer diameter	5.91 In (150 mm) 2 0.37 in ² (240 mm ²)
Net Weight	4.92 Lb(US) (2.23 kg)
Height	Outside 14.17 in (360 mm)
Width	Outside 15.35 in (390 mm)
Height	14.17 In (360 mm)
Depth	Outside 1.81 in (46 mm)
Width	15.35 In (390 mm)
Depth	1.81 In (46 mm)

Environment

IP degree of protection	Connectors IP20 IP30
Environmental characteristic	Exposure to damp heat not in service 25...55 °C, RH 95 %) 28 cycles IEC 60068-2-30 Salt mistKb/2 IEC 60068-2-52 Exposure to damp heat in servicecategory C2 48 hours IEC 60068-2-56
Pollution degree	Level 3 IEC 60664-1
Ambient air temperature for operation	-31...158 °F (-35...70 °C)
Ambient air temperature for storage	-67...185 °F (-55...85 °C)
Standards	IEC 60947-2
Product certifications	CE




Ordering and shipping details

Category	01078-DE2 MISC
Discount Schedule	DE2
GTIN	03303430504429
Nbr. of units in pkg.	1
Package weight(Lbs)	4.80 Lb(US) (2.175 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.13 In (5.4 cm)
Package 1 width	14.49 In (36.8 cm)
Package 1 Length	15.83 In (40.2 cm)
Unit Type of Package 2	S04
Number of Units in Package 2	5
Package 2 Weight	25.91 Lb(US) (11.754 kg)
Package 2 Height	11.81 In (30 cm)
Package 2 width	15.75 In (40 cm)
Package 2 Length	23.62 In (60 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	-----------------------