

Product data sheet

Characteristics

60950

ground fault protector GFP - 2 poles - 25A -
120..240V - 100mA SIE



Product availability: Stock - Normally stocked in distribution facility

Price*: 570.00 USD



Commercial status

This Product is Obsolete : FEB 17, 2021

⚠ This Product is Obsolete

Main

| | |
|---|---|
| Range | Multi 9 |
| Product name | Multi 9 GFP |
| Product or component type | Residual current circuit breaker (RCCB) |
| Device short name | GFP |
| Poles description | 2P |
| Neutral position | Left |
| Line Rated Current | 25 A |
| Network type | AC |
| Earth-leakage sensitivity | 100 MA |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type AC-SIE |
| Rated conditional short-circuit current | 10 KA |
| Utilisation category | AC-23A |

Complementary

| | |
|--|--|
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 230/240 V AC 50 Hz 120/240 V AC 60 Hz |
| [Uimp] rated impulse withstand voltage | 6 KV |
| Control type | Toggle |
| Local signalling | Fault indication |
| 9 mm pitches | 4 |
| Height | 3.19 In (81 mm) |
| Width | 1.42 In (36 mm) |
| Depth | 2.95 In (75 mm) |
| Net Weight | 7.76 Oz (220 g) |
| Color | Gray |
| Mechanical durability | 20000 Cycles |

| | |
|-----------------------------|---|
| Provision for padlocking | Padlockable |
| Locking options description | Padlocking in OFF position |
| Connections - terminals | Tunnel type terminals 0.00...0.05 in ² (2.5...35 mm ²) flexible Tunnel type terminals 0.00...0.05 in ² (2.5...35 mm ²) rigid |
| Tightening torque | 30.98 Lbf.In (3.5 N.m) |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 61008 UL 1053 |
| IP degree of protection | IP20 conforming to IEC 60529 IP40IEC 60529 IPxx BIEC 60529 |
| Tropicalisation | 2 |
| Relative humidity | 95 % 131 °F (55 °C) |
| Ambient air temperature for operation | -13...140 °F (-25...60 °C) |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |





Ordering and shipping details

| | |
|-----------------------|---------------------------------------|
| Category | 00908 - C60N SUPPLEMENTARY PROTECTORS |
| Discount Schedule | DE2 |
| GTIN | 00785901592204 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 7.65 Oz (217 g) |
| Returnability | No |
| Country of origin | ES |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.57 In (4 cm) |
| Package 1 width | 3.27 In (8.3 cm) |
| Package 1 Length | 3.54 In (9 cm) |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 6 |
| Package 2 Weight | 2.99 Lb(US) (1.357 kg) |
| Package 2 Height | 3.46 In (8.8 cm) |
| Package 2 width | 3.66 In (9.3 cm) |
| Package 2 Length | 10.04 In (25.5 cm) |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 54 |
| Package 3 Weight | 28.00 Lb(US) (12.7 kg) |
| Package 3 Height | 11.81 In (30 cm) |
| Package 3 width | 11.81 In (30 cm) |
| Package 3 Length | 15.75 In (40 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |

Environmental Disclosure [Product Environmental Profile](#)

WEEE The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty 18 months

Product Life Status : **End of commercialisation**

60950 may be replaced by any of the following products:



M9R12225

Multi9 - GFP - RCCB - 2P - 25A - class A SI - 240 V - 86 mA instantaneous

Qty 1

Substitution date: |
