

Product data sheet

Characteristics

60954

ground fault protector GFP - 2 poles - 40A - 120..240V - 300mA SIE



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 467.00 USD



Commercial status

This Product is Obsolete : JUL 12, 2021

⚠ This Product is Obsolete

Main

Range	Multi 9
Product name	Multi 9 GFP
Product or component type	Residual current circuit breaker (RCCB)
Device short name	GFP
Poles description	2P
Neutral position	Left
Line Rated Current	40 A
Network type	AC
Earth-leakage sensitivity	300 MA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type AC-SIE
Rated conditional short-circuit current	10 KA
Utilisation category	AC-23A

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	230/240 V AC 50 Hz 120/240 V AC 60 Hz
[Uimp] rated impulse withstand voltage	6 KV
Control type	Toggle
Local signalling	Fault indication
Mounting support	DIN rail
9 mm pitches	4
Height	3.19 In (81 mm)
Width	1.42 In (36 mm)
Depth	2.95 In (75 mm)
Net Weight	7.76 Oz (220 g)
Color	Gray

Mechanical durability	20000 Cycles
Provision for padlocking	Padlockable
Locking options description	Padlocking in OFF position
Connections - terminals	Tunnel type terminals 0.00...0.05 in ² (2.5...35 mm ²) flexible Tunnel type terminals 0.00...0.05 in ² (2.5...35 mm ²) rigid
Tightening torque	30.98 Lbf.In (3.5 N.m)

Environment

Standards	UL 1053 IEC 61008
IP degree of protection	IP20 conforming to IEC 60529 IP40IEC 60529 IPxx BIEC 60529
Tropicalisation	2
Relative humidity	95 % 131 °F (55 °C)
Ambient air temperature for operation	-13...140 °F (-25...60 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)

Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901576624
Nbr. of units in pkg.	1
Package weight(Lbs)	7.44 Oz (211 g)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.31 In (8.4 cm)
Package 1 width	1.61 In (4.1 cm)
Package 1 Length	3.58 In (9.1 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commercialisation**

60954 may be replaced by any of the following products:



M9R84240

Multi9 - GFP - RCCB - 2P - 40A - class A SI - 240 V - 260 mA instantaneous

Qty 1

Substitution date: |
