

# Product data sheet

## Characteristics

8501KPD12P14V53

8501 K RELAY - 240VAC - 10AMP - TYPE K  
+OPTIONS



Price\*: 45.00 USD



⚠ This Product is Obsolete

### Commercial status

This Product is Obsolete : JAN 23, 2021

#### Main

Range of product	8501K
Product or component type	Relay
Contacts material	Silver tin oxide
Switch function	DPDT
[Uc] control circuit voltage	24 V DC
Rated power in hp	0.33 Hp 120 V AC 0.5 Hp 240 V AC
Maximum switching voltage	240 V AC
Mounting support	Socket
Ambient air temperature for operation	-40...158 °F (-40...70 °C)
Shape of pin	Tubular
Product certifications	UL Recognized CSA CE
Operating time	7 ms - drop-out 18 ms - pick-up
Local signalling	Green indicator on LED
Control type	Without
Product compatibility	8501NR52 8501NR51
Relay type	General purpose

#### Ordering and shipping details

Category	21141-8501 KP
Discount Schedule	CP2
GTIN	00785901490807
Package weight(Lbs)	3.20 Oz (90.718 g)
Returnability	No
Country of origin	CN

## Packing Units

Package 1 Height	1.50 In (3.810 cm)
Package 1 width	1.50 In (3.810 cm)
Package 1 Length	2.80 In (7.112 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commercialisation**

8501KPD12P14V53 is replaced by the following product range:



**7529**

Square D® general purpose relays are suited for use as logic elements and power switching output devices.

Substitution date: |



**8501KPDR12P14V53**

Plug in relay, Type KP, tubular, 1 HP at 277 VAC, 10A resistive at 120 VAC, 8 pin, DPDT, 2 NO, 2 NC, 24 VDC coil, light

Qty 1

Substitution date: |