

Product data sheet

Characteristics

8501KU13V20

Plug-In Relay - 11 blade plug-in - 3 poles -
120VAC coil



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 24.60 USD



⚠ This Product is Obsolete

Commercial status

This Product is Obsolete : JAN 23, 2021

Main

Range of product	8501K
Product or component type	Relay
Relay type	General purpose
Mounting support	Socket
Switch function	3PDT
[Uc] control circuit voltage	120 V AC
Local signalling	No indicator
Control type	Without test button

Complementary

Rated power in hp	0.33 Hp 120 V AC 0.5 Hp 240 V AC
Rated breaking capacity	3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 10 A 28 V DC resistive control circuit UL 508 10 A 120 V AC resistive control circuit UL 508 6.66 A 240 V AC resistive control circuit UL 508
Maximum switching voltage	300 V AC 30 V DC
Contacts material	Silver tin oxide
Operating time	8 ms - pick-up 8 ms - drop-out
Shape of pin	Spade
Product compatibility	8501NR82

Environment

Ambient air temperature for operation	-40...113 °F (-40...45 °C)
Product certifications	UL Listed CE CSA UL Recognized
Height	2.07 in (52.58 mm)
Width	1.52 in (38.61 mm)
Depth	1.42 in (36.07 mm)

Ordering and shipping details

Category	21144 - 8501 KU
Discount Schedule	CP2
GTIN	00785901480808
Nbr. of units in pkg.	1
Package weight(Lbs)	0.19 Lb(US) (0.09 kg)
Returnability	No
Country of origin	CN

Packing Units

Package 1 Height	2.28 in (5.800 cm)
Package 1 width	1.61 in (4.100 cm)
Package 1 Length	1.50 in (3.800 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commercialisation**

8501KU13V20 is replaced by the following product range:



7529

Square D® general purpose relays are suited for use as logic elements and power switching output devices.

Substitution date: |



8501KUR13V20

Plug in relay, Type KU, blade, 0.5 HP at 240 VAC, 10A resistive at 120 VAC, 11 blade, 3PDT, 3 NO, 3 NC, 120 VAC coil

Qty 1

Substitution date: |
