

Product data sheet

Characteristics

8502SEG2V02S

NEMA Contactor, Type S, nonreversing, Size 3, 90A, 50 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 120 VAC coil, NEMA 1



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1715.00 USD



Main

Product or Component Type	Contacteur
Range of Product	8502S
Contacteur application	Non-reversing

Complementary

NEMA size	3
Line Rated Current	90 A
Poles description	3P
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Rated power in HP	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC
Product compatibility	Circuit-breaker 150 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Control circuit	Separate control circuit
Control type	No control units
Local signalling	No indicator
Auxiliary contact composition	Without
Provided Equipment	Fuse not supplied
Electrical Connection	Screw clamp terminals
Maximum Height	21.81 In (554 mm)

Maximum Width	11.46 In (291 mm)
Maximum Depth	7.99 In (203 mm)

Environmental

NEMA degree of protection	NEMA 1 painted sheet steel
Product Certifications	UL listed file E78351 CCN NLDX CSA



Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901788027
Nbr. of units in pkg.	1
Package weight(Lbs)	32.73 Lb(US) (14.85 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	9.00 In (22.860 cm)
Package 1 width	11.90 In (30.226 cm)
Package 1 Length	22.10 In (56.134 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**