

Product data sheet

Characteristics

8502SEO2V03

NEMA Contactor, Type S, nonreversing, Size 3, 90A, 50 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 240 VAC coil, open



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1425.00 USD



Main

Product or Component Type	Contacteur
Range of Product	8502S
Contacteur application	Non-reversing

Complementary

NEMA size	3
Line Rated Current	90 A
Poles description	3P
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Rated power in HP	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC
Product compatibility	Circuit-breaker 150 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC
[Uc] control circuit voltage	240 V AC 60 Hz 220 V AC 50 Hz
Control circuit	Common control circuit
Control type	No control units
Local signalling	No indicator
Auxiliary contact composition	Without
Provided Equipment	Fuse not supplied
Electrical Connection	Screw clamp terminals
Maximum Height	7.09 In (180.09 mm)

Maximum Width	5.47 In (138.94 mm)
Maximum Depth	6.50 In (165.10 mm)

Environmental

NEMA degree of protection	Not rated (open device)
Product Certifications	UL listed file E78351 CCN NLDX CSA

Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901788119
Nbr. of units in pkg.	1
Package weight(Lbs)	13.10 Lb(US) (5.942 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.50 In (19.05 cm)
Package 1 width	9.10 In (23.114 cm)
Package 1 Length	14.30 In (36.322 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**