

# Product data sheet

## Characteristics

# 8502SHO2V03

NEMA Contactor, Type S, nonreversing, Size 6, 540A, 400 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 240 VAC coil, open



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 20339.00 USD



### Main

Product or Component Type	Contacteur
Range of Product	8502S
Contacteur application	Non-reversing

### Complementary

NEMA size	6
Line Rated Current	540 A
Poles description	3P
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Rated power in HP	150 HP 200 V AC 200 HP 230 V AC 400 HP 460 V AC 400 HP 575 V AC
Product compatibility	Circuit-breaker 800 A maximum, SCCR: 65 kA at 480 V AC Fuse J 600 A maximum, SCCR: 100 kA at 600 V AC Fuse T 600 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 600 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 600 A maximum, SCCR: 100 kA at 600 V AC
[Uc] control circuit voltage	240 V AC 60 Hz 220 V AC 50 Hz
Control circuit	Control circuit transformer
Control type	No control units
Local signalling	No indicator
Auxiliary contact composition	Without
Provided Equipment	2 fuses (primary)
Electrical Connection	Screw clamp terminals
Maximum Height	28.06 In (712.72 mm)

Maximum Width	10.55 In (267.97 mm)
Maximum Depth	9.00 In (228.60 mm)

### Environmental

NEMA degree of protection	Not rated (open device)
Product Certifications	UL listed file E78351 CCN NLDX CSA

### Ordering and shipping details

Category	21195 - 8502,36 SH,SJ(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901882688
Nbr. of units in pkg.	1
Package weight(Lbs)	77.4 Lb(US) (35.11 kg)
Returnability	Yes
Country of origin	MX

### Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**