

Product data sheet

Characteristics

8536SBG2V03

NEMA Motor Starter, Type S, nonreversing, Size 0, 18A, 5 HP at 460 VAC, 5 kA SCCR, 3 phase, 3 pole, melting alloy, 240 VAC coil, NEMA 1



Product availability: Stock - Normally stocked in distribution facility

Price*: 518.00 USD



Main

Product or component type	Motor starter
Range of product	S
Motor starter type	Non reversing

Complementary

NEMA size	0
Line Rated Current	18 A
Poles description	3P
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Thermal overload type	Melting alloy 3
Rated power in HP	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC
Product compatibility	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC
[Uc] control circuit voltage	220 V AC 50 Hz 240 V AC 60 Hz
Control circuit	Common control circuit
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Electrical connection	Screw clamp terminals
Height	10.00 In (254.00 mm)
Width	6.00 In (152.40 mm)
Depth	5.56 In (141.22 mm)

Environment

NEMA degree of protection	NEMA 1 painted sheet steel
Product certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901869108
Nbr. of units in pkg.	1
Package weight(Lbs)	7.41 Lb(US) (3.36 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.98 In (15.2 cm)
Package 1 width	6.42 In (16.3 cm)
Package 1 Length	11.50 In (29.2 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**