

Product data sheet

Characteristics

8536SCG2V02S

NEMA Motor Starter, Type S, nonreversing, Size 1P, 36A, 5 HP at 230 VAC, 5 kA SCCR, 1 phase, 2 pole, melting alloy, 120 VAC coil, NEMA 1



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 696.00 USD



Main

Product or Component Type	Motor starter
Range of Product	S
Motor starter type	Non reversing

Complementary

NEMA size	1P
Line Rated Current	36 A
Poles description	2P
[Ue] rated operational voltage	600 V AC
Phase	1 phase
Thermal overload type	Melting alloy 1
Rated power in HP	3 HP 115 V AC 5 HP 230 V AC
Product compatibility	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control circuit	Separate control circuit
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Electrical Connection	Screw clamp terminals
Maximum Height	10.00 In (254.00 mm)
Maximum Width	6.00 In (152.40 mm)
Maximum Depth	5.56 In (141.22 mm)

Environment

NEMA degree of protection	NEMA 1 painted sheet steel
Product Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901094500
Nbr. of units in pkg.	1
Package weight(Lbs)	7.16 Lb(US) (3.25 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	6.50 In (16.510 cm)
Package 1 width	6.50 In (16.510 cm)
Package 1 Length	10.50 In (26.670 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**