

Product data sheet

Characteristics

8536SCO3V02H300S

NEMA Motor Starter, Type S, nonreversing, Size 1, 27A, 10 HP at 460 VAC, up to 100 kA SCCR, 3 phase, 3 pole, Motor Logic, 120 VAC coil, open



Product availability: Stock - Normally stocked in distribution facility

Price*: 650.00 USD



Main

Product or Component Type	Motor starter
Range of Product	S
Motor starter type	Non reversing

Complementary

NEMA size	1
Line Rated Current	27 A
Poles description	3P
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Thermal overload type	Solid state Motor Logic class 10/20
Rated power in HP	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC
Product compatibility	Circuit-breaker 70 A maximum: 100 kA at 480 V AC Fuse J 60 A maximum: 100 kA at 600 V AC Fuse T 60 A maximum: 100 kA at 600 V AC Fuse RK1 60 A maximum: 100 kA at 600 V AC Fuse RK5 60 A maximum: 100 kA at 600 V AC
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control circuit	Separate control circuit
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Electrical Connection	Screw clamp terminals
Maximum Height	6.81 In (172.96 mm)

Maximum Width	3.50 In (88.90 mm)
Maximum Depth	4.22 In (107.19 mm)

Environment

NEMA degree of protection	Not rated (open device)
Product Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901836773
Nbr. of units in pkg.	1
Package weight(Lbs)	3.99 Lb(US) (1.81 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.41 In (11.2 cm)
Package 1 width	5.91 In (15 cm)
Package 1 Length	7.91 In (20.1 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**