

Product data sheet

Characteristics

8536SDA1V06

NEMA Motor Starter, Type S, nonreversing, Size 2, 45A, 25 HP at 460 VAC, 5 kA SCCR, 3 phase, 3 pole, melting alloy, 480 VAC coil, NEMA 12



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1472.00 USD



Main

Product or Component Type	Motor starter
Range of Product	S
Motor starter type	Non reversing

Complementary

NEMA size	2
Line Rated Current	45 A
Poles description	3P
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Thermal overload type	Melting alloy 3
Rated power in HP	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC
Product compatibility	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz
Control circuit	Common control circuit
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Electrical Connection	Screw clamp terminals
Maximum Height	16.00 In (406.40 mm)
Maximum Width	8.13 In (206.50 mm)
Maximum Depth	9.28 In (235.71 mm)

Environment

NEMA degree of protection	NEMA 12 painted sheet steel
Product Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901890812
Nbr. of units in pkg.	1
Package weight(Lbs)	21.66 Lb(US) (9.825 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.50 In (26.67 cm)
Package 1 width	10.70 In (27.178 cm)
Package 1 Length	16.80 In (42.672 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**