

# Product data sheet

## Characteristics

# 8536SFG1V02S

NEMA Motor Starter, Type S, nonreversing, Size 4, 135A, 100 HP at 460 VAC, 3 phase, 3 pole, melting alloy, 120 VAC coil, NEMA 1, 10 kA SSCR



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 4350.00 USD



### Main

Product or Component Type	Motor starter
Range of Product	S
Motor starter type	Non reversing

### Complementary

NEMA size	4
Line Rated Current	135 A
Poles description	3P
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Thermal overload type	Melting alloy 3
Rated power in HP	40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC
Product compatibility	Circuit-breaker: 10 kA at 600 V AC Fuse: 10 kA at 600 V AC
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control circuit	Separate control circuit
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Electrical Connection	Screw clamp terminals
Maximum Height	25.16 In (639.06 mm)
Maximum Width	11.25 In (285.75 mm)
Maximum Depth	9.00 In (228.60 mm)

## Environment

NEMA degree of protection	NEMA 1 painted sheet steel
Product Certifications	UL Listed CSA NEMA

## Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901832232
Nbr. of units in pkg.	1
Package weight(Lbs)	43.31 Lb(US) (19.645 kg)
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.60 In (26.924 cm)
Package 1 width	11.90 In (30.226 cm)
Package 1 Length	25.50 In (64.77 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**