

Product data sheet

Characteristics

8536SHO2V06

NEMA Motor Starter, Type S, nonreversing, Size 6, 540A, 400 HP at 460 VAC, 3 phase, 3 pole, melting alloy, 480 VAC coil, open



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 32634.00 USD



Main

Product or Component Type	Motor starter
Range of Product	S
Motor starter type	Non reversing

Complementary

NEMA size	6
Line Rated Current	540 A
Poles description	3P
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Thermal overload type	Melting alloy 3
Rated power in HP	150 HP 200 V AC 200 HP 230 V AC 400 HP 460 V AC 400 HP 575 V AC
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz
Control circuit	Control circuit transformer
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Provided Equipment	2 fuses (primary), 2 fuses (secondary)
Electrical Connection	Screw clamp terminals
Maximum Height	28.06 In (712.72 mm)
Maximum Width	12.34 In (313.44 mm)
Maximum Depth	9.00 In (228.60 mm)

Environment

NEMA degree of protection	Not rated (open device)
Product Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21195 - 8502,36 SH,SJ(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901619796
Nbr. of units in pkg.	1
Package weight(Lbs)	1 Lb(US) (0.45 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**