

Product data sheet

Characteristics

8538SBA23V81CF4T

NEMA Combination Starter, Type S, 30A fusible disconnect, Size 0, 18A, 5HP at 600VAC, 3 phase, 3 pole, melting alloy, 120VAC coil, NEMA 12



Price*: 2406.00 USD



Main

Product or Component Type	Combination Starter
Range of Product	S
Control circuit	Control circuit transformer

Complementary

[Uc] control circuit voltage	120 V AC 60 Hz secondary circuit 480 V AC 60 Hz primary circuit
Motor starter type	Non reversing
Line Rated Current	18 A
Poles description	3P
Maximum Horse Power Rating	5 Hp 460 V AC, 3 phase 5 Hp 575 V AC, 3 phase
[Ue] rated operational voltage	600 V AC
Control type	Selector switch HAND-OFF-AUTO)
Local signalling	No indicator
Auxiliary contact composition	Without
Provided equipment	2 fuses primary circuit
Thermal overload type	Melting alloy 3
Disconnecter device type	Fusible disconnect switch H, 30 A
NEMA size	0
Maximum Height	24 In (609.60 mm)
Maximum Depth	8.34 In (211.84 mm)
Maximum Width	9.50 In (241.30 mm)

Environment

NEMA degree of protection	NEMA 12 painted sheet steel with external reset
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	21212-8538,39SB(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	00785901019565
Package weight(Lbs)	45.00 Lb(US) (20.412 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**