

Product data sheet

Characteristics

8538SBG12V03

NEMA Combination Starter, Type S, 30A fusible disconnect, Size 0, 18A, 3 HP at 240 VAC polyphase, 240 VAC coil, NEMA 1



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product or Component Type	Combination Starter
Range of Product	S
Control circuit	Common control circuit

Complementary

[Uc] control circuit voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Poles description	3P
Maximum Horse Power Rating	3 Hp 200 V AC, 3 phase 3 Hp 230 V AC, 3 phase
[Ue] rated operational voltage	600 V AC
Control type	No control units
Local signalling	No indicator
Auxiliary contact composition	Without
Thermal overload type	Melting alloy 3
Disconnecter device type	Fusible disconnect switch H, 30 A
NEMA size	0

Environment

NEMA degree of protection	NEMA 1 painted sheet steel with external reset
---------------------------	--

Ordering and shipping details

Category	21212 - 8538,39SB(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	00785901744009
Nbr. of units in pkg.	1
Package weight(Lbs)	30.53 Lb(US) (13.848 kg)

Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.50 In (26.67 cm)
Package 1 width	10.50 In (26.67 cm)
Package 1 Length	25.60 In (65.024 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	-----------------------