

# Product data sheet

## Characteristics

# 8538SCA44V02S

NEMA Combination Starter, Type S, 30A fusible disconnect, Size 1, 27A, 10 HP at 600 VAC polyphase, 120 VAC coil, NEMA 12



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 1808.00 USD



### Main

Product or Component Type	Combination Starter
Range of Product	S
Control circuit	Separate control circuit

### Complementary

[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Line Rated Current	27 A
Poles description	3P
Maximum Horse Power Rating	10 Hp 460 V AC, 3 phase 10 Hp 575 V AC, 3 phase
[Ue] rated operational voltage	600 V AC
Control type	No control units
Local signalling	No indicator
Auxiliary contact composition	Without
Thermal overload type	Melting alloy 3
Disconnecter device type	Fusible disconnect switch R, 30 A
NEMA size	1
Maximum Height	24.0 In (609.60 mm)
Maximum Depth	9.5 In (241.30 mm)
Maximum Width	8.34 In (211.84 mm)

### Environment

NEMA degree of protection	NEMA 12 painted sheet steel with external reset
Product Certifications	UL CSA

## Ordering and shipping details

Category	21213 - 8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901021063
Nbr. of units in pkg.	1
Package weight(Lbs)	32.85 Lb(US) (14.90 kg)
Returnability	No
Country of origin	MX

## Packing Units

Package 1 Height	11.00 In (27.940 cm)
Package 1 width	13.10 In (33.274 cm)
Package 1 Length	29.00 In (73.660 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**