

Product data sheet

Characteristics

8539SFA15V02S

NEMA Combination Starter, Type S, 150A JLL thermal magnetic circuit breaker, Size 4, 135A, 3 phase, 120VAC coil, NEMA 12



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product or Component Type	Combination Starter
Range of Product	S
Control circuit	Separate control circuit

Complementary

[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Poles description	3P
Maximum Horse Power Rating	60 Hp 460 V AC, 3 phase 60...75 Hp 575 V AC, 3 phase
[Ue] rated operational voltage	600 V AC
Control type	No control units
Local signalling	No indicator
Auxiliary contact composition	Without
Thermal overload type	Melting alloy 3
Disconnecter device type	Thermal magnetic circuit breaker, 110 A

Environment


NEMA degree of protection	NEMA 12 painted sheet steel with external reset
NEMA size	4

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	21214 - 8538,39 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
Nbr. of units in pkg.	1
Package weight(Lbs)	170 Lb(US) (77.11 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**