

Product data sheet

Characteristics

8702SEO2V02S

NEMA Contactor, Type S, reversing, Size 3, 90A,
3 pole, 3 phase, horizontal, 110/120 VAC 50/60
Hz coil, open style



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 3689.00 USD



Main

Product or Component Type	Contacteur
Range of Product	Type S
Contacteur application	Reversing

Complementary

NEMA size	3
Line Rated Current	90 A
Poles description	3P
Condition of use	Horizontal
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Rated power in HP	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control circuit	Separate control circuit
Control type	No control units
Provided Equipment	Fuse not supplied
Electrical Connection	Screw clamp terminals
Maximum Height	7.95 In (202 mm)
Maximum Width	12.72 In (323 mm)
Maximum Depth	7.01 In (178 mm)

Environment

NEMA degree of protection	Not rated (open device)
Product Certifications	UL Listed CSA


Ordering and shipping details

Category	21273 - 8702,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901808916
Nbr. of units in pkg.	1
Package weight(Lbs)	17 Lb(US) (7.71 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	10.60 In (26.924 cm)
Package 1 width	17.80 In (45.212 cm)
Package 1 Length	26.80 In (68.072 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**